



GRAVITY SEWER PIPE REHABILITATION

SPIRAL WOUND LINING – PERFORMANCE SPECIFICATION GUIDELINE

Document No. ESF-600-STD-208

Version: 1.0

Published Date: 17 March 2025

Copyright information

Copyright © Watercare Services Limited. All rights reserved.

Disclaimer

Watercare Services Limited has endeavoured to ensure material in this document is technically accurate and reflects legal requirements. However, the document does not override governing legislation.

Watercare Services Limited does not accept liability for any consequences arising from the use of this document. If the user of this document is unsure whether the material is correct, they should refer directly to the relevant legislation and contact Watercare Services Limited.

More information

If you have further queries, please contact the Asset Lifecycle team at standards@water.co.nz

DOCUMENT CONTROL

Document owner Principal Asset Lifecycle Engineer (Standards)

Review Head of Sustainability and Innovation

Version history

Version	Description of revision	Prepared by	Approved by	Date
1.0	First release	W Strydom	B Harkness	17-03-2025

This document takes effect on the date of release and supersedes all prior versions.

Acknowledgements

We would like to acknowledge the contributions made by those listed below, reviewing these documents and providing valued feedback.

Ben Pritchard (Jacobs)

Blair Telfer (Australasian Society for Trenchless Technology)

Husham Al-Saleem (Project Max)

Ian Bateman (Pipecare)

Mark Thomson (Project Max)

Martin Spies (Pipecare)

Matt Thomsson (Jacobs)

Philip McFarlane (WSP)

Stefan Foster (Abergeldie)

Steve Apeldoorn (Project Max)

Definitions

ASTM	American Society for Testing Materials
ASTT	Australasian Society for Trenchless Technology
CCTV	Closed Circuit Television – which includes cameras and displays to record and inspect pipelines.
Contractor	Main contractor engaged by Watercare, responsible for delivering the works
Defect	Any discontinuity, imperfection or inclusion arising from substandard materials, improper pipe preparation, or faulty manufacture, installation or workmanship which affects the hydraulic or structural performance of the lining
Flow management plan (FMP)	Contractor plan(s) and methods to divert flows whilst preventing overflows or any adverse consequences whilst preparing the host pipe and installing the new liner.
IANZ	International Accreditation New Zealand
ISO	International Organisation for Standardisation
Lateral Junction repair (LJR)	Repair made with CIPP technology to a damaged lateral connection, either stand alone or in conjunction with a full or part liner
MSWL	Machine spiral wound liners
NDSRs	No-dig spot repairs
Project Specification	Project specific requirements specific by the design engineer which form part of the minimum requirements to be met during construction
PVC-U	Unplasticized polyvinyl chloride
Quality Control Plan	The Contractor's documentation that defines the procedures for delivering the level of construction quality required by the project.
SGSWL	Structural grout spiral wound liners
Specialist Contractor	Contractor carrying out the physical installation of the liner in accordance with the project specifications and manufacturer's recommendations.

Spiral wound lining	Linings installed by the spiral winding of a profiled strip to form a continuous pipe
Watercare	Watercare's representative responsible for managing the project.

Table of Contents

DEFINITIONS	4
1. SCOPE	7
1.1 OVERVIEW.....	7
2. RELEVANT STANDARDS	7
3. DESIGN	8
4. MATERIAL REQUIREMENTS	9
4.1 MATERIAL PROPERTIES.....	9
4.2 PROFILE.....	9
4.3 CHEMICAL, TEMPERATURE AND ABRASION RESISTANCE	9
5. CONSTRUCTION	9
5.1 INSTALLATION	9
5.1.1 Liner installation.....	9
5.1.2 Defects	10
6. ACCEPTANCE CONTROL.....	10
6.1 TESTING	10
6.1.1 Leak testing	10
6.2 SAMPLING	11
APPENDIX A: EXAMPLE INSPECTION AND TEST PLAN	12

1. Scope

This Performance Specification includes the minimum requirements for the rehabilitation of pipelines using spiral wound liners. These liners are installed using continuous strips of profiled PVC-U sections into a spirally wound pipe (or liner) that fits into an existing pipe.

Spiral wound liners can be categorised as either Machine Spiral Wound Liners (MSWL) or Structural Grout Spiral Wound Liners (SGSWL). MSWL are generally used for smaller diameter (non-person entry) pipelines, where SGSWL are considered for larger diameter sewers where liners are installed tight against the pipe wall or constructed to a predetermined size prior to installation.

This document shall be read in conjunction *ESF-600-STD-206: Gravity sewer pipe rehabilitation – General requirements for the installation of lining systems*.

1.1 Overview

The lining shall be a PVC-U profile, field-fabricated into a spiral wound liner pipe. After insertion, the spiral wound liner pipe shall expand to meet the interior surface of the existing pipeline or installed in a manner that the profile is wound tight against the pipe wall in the case of SGSWL methods. Alternatively, the spiral wound liner pipe can be inserted into the existing pipe after it has been manufactured to a fixed diameter, and the annular space between the spiral wound liner pipe and the existing pipe is grouted.

Table 1: Application of spiral wound liners

Reference	Description
Liner material	PVC-U
Roughness coefficient	0.009 mm
Liner Classification	Class A – Fully structural Class B – Semi-structural Class C – Semi-structural
Applications	Wastewater: Non-pressure
Pipe sizes	150mm to 1800mm diameter
Installation	Manhole to manhole
Design life	50 years

2. Relevant Standards

Table 2: Standards applicable to spiral wound PVC-U liners

Standard	Relevance	Applicable SWL method
AS/NZS ISO 11295: Plastics piping systems used for the rehabilitation of pipelines - Classification and overview of strategic, tactical and operational activities	Planning and general	All – General
AS/NZS ISO 11296.1: Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks, Part 1: General	General	All
AS/NZS ISO 11296.7: Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks - Part 7: Lining with spirally-wound pipes	Design, materials and testing	
ASTT – DS-D001: Design for Structural Renovation of Pipelines by Internal Lining, Part 1 – Circular Non-pressure Pipelines	Design	

Standard	Relevance	Applicable SWL method
ASTM F1741: Standard Practice for Installation of Machine Spiral-Wound Poly (Vinyl Chloride) (PVC) Liner Pipe Rehabilitation of Existing Sewers and Conduit	Design and Installation	Machine spiral wound liners (MSWL)
ASTM F1697: Standard Specification for Poly (Vinyl Chloride) (PVC) Profile Strip for Machine Spiral-Wound Liner Pipe Rehabilitation of Existing Sewers and Conduits	Installation, materials and testing	
ASTM F1735: Standard Specification for Poly (Vinyl Chloride) (PVC) Profile Strip for PVC Liners for Rehabilitation of Existing Man-Entry Sewers and Conduits	Material	Structural grout spiral wound liners (SGSWL)
ASTM F1698: Standard Practice for Installation of Poly (Vinyl Chloride) (PVC) Profile Strip and Cementitious Grout for Rehabilitation of Existing Man-Entry Sewers and Conduits	Installation, materials and testing	
ASTM D638: Standard Test Method for Tensile Properties of Plastics	Material and testing	All
ASTM D790: Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials	Material and testing	
ISO 23818-3: Assessment of conformity of plastics piping systems for the rehabilitation of existing pipelines - Part 3: Unplasticised poly(vinyl chloride) (PVC-U) material	Material and testing	
ASTM D543: Standard Practices for Evaluating the Resistance of Plastics to Chemical Reagents.	Material	

Note: The latest revisions of the standards listed above shall be referred to when carrying out any of the associated works.

3. Design

Design of the lining system shall meet all the relevant requirements of *ESF-600-STD-206: Gravity sewer pipe rehabilitation – General requirements for the installation of lining systems*.

The spiral wound liner shall be designed using one of the following standards:

- Machine spiral wound liners (MSWL)
 - ASTT – DS-D001 Specification:** Design for Structural Renovation of Pipelines by Internal Lining, Part 1 – Circular Non-pressure Pipelines
 - ASTM F1741:** Standard Practice for Installation of Machine Spiral-Wound Poly (Vinyl Chloride) (PVC) Liner Pipe Rehabilitation of Existing Sewers and Conduit – Appendix X1
- Structural grout spiral wound liners (SGSWL)
 - ASTM F1698:** Standard Practice for Installation of Poly (Vinyl Chloride) (PVC) Profile Strip and Cementitious Grout for Rehabilitation of Existing Man-Entry Sewers and Conduits – Appendix X1

The long term (50 year extrapolated) Creep Reduction Factor shall be set at 50% of the initial flexural modulus as determined by ASTM D790 test method. This value shall be used unless the Contractor submits long term test data (ASTM D2990) to substantiate a higher retention factor.

The lining shall be designed and fabricated in a manner that, when installed, will fit the internal wall and length of the pipe being lined, within the tolerances specified by the designer.

All work on the preparation of the design calculations, including proof checking and review, shall be included in the Contractor's quality assurance documentation.

4. Material requirements

4.1 Material properties

The Contractor shall submit test data to substantiate that the values for material properties nominated in the design calculations can be achieved by the materials supplied for the pipeline installation.

Where material properties under load vary with time, material properties of the lining at the end of the 50-year design life shall be used in design calculations. The exception to this is design of the lining for loads applied only during installation, which may be based on short-term material properties.

The material properties of the lining material used in the rehabilitation of the pipeline shall be consistent with the design properties. These properties shall have the same values as those nominated by the Designer.

4.2 Profile

The spiral wound liner profile shall meet the requirements set out in the following standards:

- Machine spiral wound liners (MSWL)
 - **ASTM F1697:** Standard Specification for Poly (Vinyl Chloride) (PVC) Profile Strip for Machine Spiral-Wound Liner Pipe Rehabilitation of Existing Sewers and Conduits
- Structural grout spiral wound liners (SGSWL)
 - **ASTM F1735:** Standard Specification for Poly (Vinyl Chloride) (PVC) Profile Strip for PVC Liners for Rehabilitation of Existing Man-Entry Sewers and Conduits

4.3 Chemical, temperature and abrasion resistance

The contractor shall provide evidence that the materials proposed, meet the applicable standards listed in this document. Refer to *ESF-600-STD-206: Gravity sewer pipe rehabilitation – General requirements for the installation of lining systems*, Section 4.3.

5. Construction

For all general construction requirements refer to *ESF-600-STD-206: Gravity sewer pipe rehabilitation – General requirements for the installation of lining systems*.

5.1 Installation

5.1.1 Liner installation

The liner installation shall be in accordance with the following standards and shall be installed as per the liner manufacturer's specification:

- Machine spiral wound liners (MSWL)
 - **ASTM F1697:** Standard Specification for Poly (Vinyl Chloride) (PVC) Profile Strip for Machine Spiral-Wound Liner Pipe Rehabilitation of Existing Sewers and Conduits
 - **ASTM F1741:** Standard Practice for Installation of Machine Spiral-Wound Poly (Vinyl Chloride) (PVC) Liner Pipe Rehabilitation of Existing Sewers and Conduit
- Structural grout spiral wound liners (SGSWL)
 - **ASTM F1698:** Standard Practice for Installation of Poly (Vinyl Chloride) (PVC) Profile Strip and Cementitious Grout for Rehabilitation of Existing Man-Entry Sewers and Conduits

There shall be no defects or discontinuities that could adversely affect the hydraulic performance or long-term life of the lining.

5.1.2 Defects

Liners shall be assessed for defects as per the relevant requirements of Section 5.2.10 of *ESF-600-STD-206: Gravity sewer pipe rehabilitation – General requirements for the installation of lining systems*.

The following are common examples of defects that are considered unacceptable and must be remediated:

- Liner installed over debris.
- Liner installed over unacceptable protrusions or deformations in the host pipe.
- Under-strength finished liner materials – short term flexural strength or modulus is less than the respective design value declared in the design.
- Defective joints e.g. popped lock in spiral wound lining.
- Leakage observed through the liner.
- Poor quality cut outs or misalignment of cut out with lateral connections / LJR's.
- Inadequate seals at manholes or lateral connections
- Liner thickness installed is less than specified design value (incorrect procurement of liner).
- Liner not fully expanded

Note: The defects listed above are not intended to be an exhaustive list. Installed liners will be assessed to confirm they meet the functional requirements over the design life of the lining system.

6. Acceptance Control

Refer to *ESF-600-STD-206: Gravity sewer pipe rehabilitation – General requirements for the installation of lining systems*.

6.1 Testing

6.1.1 Leak testing

Refer to *ESF-600-STD-206: Gravity sewer pipe rehabilitation – General requirements for the installation of lining systems*.

6.2 Sampling

The Contractor shall retain a sample of the profile from each liner section between upstream and downstream manhole and record the batch number of the profile. If grouting is undertaken (on pipes larger than DN375), it shall be sampled and tested in accordance with ASTM F1741.

Material shall also be assessed and tested to demonstrate conformity with:

- **ASTM F1697:** Standard Specification for Poly (Vinyl Chloride) (PVC) Profile Strip for Machine Spiral-Wound Liner Pipe Rehabilitation of Existing Sewers and Conduits
- **ISO 23818-3:** Assessment of conformity of plastics piping systems for the rehabilitation of existing pipelines — Part 3: Unplasticised poly (vinyl chloride) (PVC-U) material.

Page 12 of 12